





**低压电流互感器 户内干式****Current transformer drying type wed indoors****5-100/5 Overall Dimension**

额定电流比(A) Rated current ratio	L	I	ΦD
150-400/5	170	140	13
600-1000/5	210	170	19

**150-1000/5 Overall Dimension****LQG-0.5 型电流互感器****LQG-0.5 Current transformer****概述 Description**

本型电流互感器适用于额定频率为50Hz或60Hz、额定电压为0.5kV及以下的电力系统中，作电能计量、电流测量和继电保护用。

The current transformer is used for measuring electric energy and current, relay protection in the electric system up to rated frequency 50Hz or 60Hz and rated voltage 0.5kV.

**型号含义 Type designation****L Q G - 0 . 5**

—— 电压等级, kV(voltage grade , kV)  
 —— 改进线(improvement type)  
 —— 线圈式(winding type)  
 —— 电流互感器(current transformer)

**结构简介 Construction**

本型电流互感器的铁心由条形硅钢片叠成，铁心由钢板冲成的夹件固定，夹件底部有安装孔。

The iron core of his product is piled up by silicon steel sheet and fixed by the nip. There have some holes for installed on the bottom.

**技术参数 Technical data**

额定一次电流 Rated primary current(A)	额定二次电流 Rated secondary current(A)	额定输出 Rated output (VA)			额定短时热电流 (I th) Rated short-time thermal current(kA)	额定动稳定电流 (I dyn) Rated dynamic current (kA)
		0.2	0.5	1		
5,10,15,20,30						
40,50,75,100						
150,200,300		5			50 Iln	100 Iln
400,600,800			10	10		
1000				15		

**订货须知 When ordering, please specify the following**

1. 绝缘等级;
  2. 电流比;
  3. 准确级次及额定二次负荷;
  4. 使用环境。
1. Insulation level;
  2. Ratio primary and secondary current;
  3. number of cores, output ad accuracy class;
  4. Test specification.