



LZW32-10G2 型户外电流互感器

LZW32-10G2 type outdoor Current transformer

适用于ZW32户外真空断路器

Used Zw32 vacuum circuit-breaker Outdoor

技术参数 Technical data

产品型号 type	额定电流比 Rated transformation ratio(A)	级次组合 Accuracy classes combination	准确级及额定输出(vA) Accuracy class and rated output $\text{COS } \phi = 0.8$				额定短时热电流 (I _{th})Rated short-time dynamic current(kA)	额定动稳定电流 (I _{dyn})Rated dynamic current(kA)			
LZW32-10G2	50/5	10P10			10		9	22.5			
	75/5						13.5	33.8			
	100/5						18	45			
	150/5						27	67.5			
	200/5						36	90			
	300/5						36	90			
	400/5	15				40	100				
	600/5					48	120				
	630/5	10P10				48	120				
	50-75 -100/5					9	22.5				
	75-100-150/5					13.5	33.8				
	100/150-200/5					10				18	45
	150-200-300/5									27	67.5
	200-300-400/5					15				36	90
200-400-600/5	48									120	
200-400-630/5	48									120	

注：可根据用户要求制做多变比或特殊规格，多变比互感器在使用时只能使用其中一个变比，几个变比不能同时使用。

Note: Consumer such as have thfe special requirement and was negotiated by both parties certainty, the current transformer can but using one of thfe transfor mation ratios, and that can' t using several transformation ration at the same time.